## Bakaiya Rural Municipality Office of Rural Municipal Executive Hattisunde, Makawanpur Bagmati Province, Nepal

## 1. Technical Specification of Tractor

CRITERIA	REQUIREMENT
General	Farm Tractor, Four Wheel drive, suitable for farm work driving giving smooth economic performance and in suitable for hilly area in Nepal Ground Clearance should be minimum 360 mm. Total weight of vehicle shall not be less than 2000 kgs. 4WD.
Engine	4-Stroke, min. 3 cylinders water cooled Diesel Engine developing maximum rated power output not less than 60 HP category at rated rpm, Rotary type fue injection pump will be highly preferred. 2023 mode or above.
Gauges	To include speedometer, water temperature, as necessary for efficient operation and maintenance.
Clutch	Dual clutch (diaphragm Clutch / Dry type) or suitable for Transmission.
Transmission	Manual shift at least eight forward and two reverse gears (Constant mesh / Synchromesh gear mesh type)
Chassis and Frame	Steel heavy Duty with toe-hooks.
Hydraulic Lifting capacity	Not less than 2000 kg
Fuel tank	Not less than 58 litres.
Air cleaner	Oil Bathed /Dry type
Cooling System	Water cooling
Weight	More than 2000 Kg

OIJ CONTRACTOR OF THE PARTY OF



## Bakaiya Rural Municipality Office of Rural Municipal Executive Hattisunde, Makawanpur Bagmati Province, Nepal

## 1. Technical Specification of Tractor

CRITERIA	REQUIREMENT
General	Farm Tractor, Four Wheel drive, suitable for farm work driving giving smooth economic performance and in suitable for hilly area in Nepal Ground Clearance should be minimum 360 mm. Total weight of vehicle shall not be less than 2000 kgs. 4WD.
Engine	4-Stroke, min. 3 cylinders water cooled Diesel Engine, developing maximum rated power output not less than 60 HP category at rated rpm, Rotary type fuel injection pump will be highly preferred. 2023 model or above.
Gauges	To include speedometer, water temperature, as necessary for efficient operation and maintenance.
Clutch	Dual clutch (diaphragm Clutch / Dry type) or suitable for Transmission.
Transmission	Manual shift at least eight forward and two reverse gears (Constant mesh / Synchromesh gear mesh type)
Chassis and Frame	Steel heavy Duty with toe-hooks.
Hydraulic Lifting capacity	Not less than 2000 kg
Fuel tank	Not less than 58 litres.
Air cleaner	Oil Bathed /Dry type
Cooling System	Water cooling
Weight	More than 2000 Kg
and the second s	





Minimum 2000mm.
Standard size suitable for operation in hilly area too.
3 Point hitching system
Power Steering
Suspended type / Oil immersed brake
1. Head light, reversing light and turn signals
2. Speedometer / odometer, Standard tool set with jack and handle.
3 Equipped with all accessories offered in standard model but not limited to the above items. The accessories / features supplied with the tractor shall be as per manufacturer's standard.
All signs and instructions in the vehicle shall be in English.
One copy of the Operator's and Owner's Instructions in English shall be supplied with each vehicle.
A set of tools as required for general maintenance shall be supplied.
Standard colour
The bidder shall provide the manufacturer's data of the performance of the unit to include the fuel consumption, performance curve of the engine.
Manufacturer shall provide a minimum of Two-year warranty after acceptance.
The supplier shall provide the vehicle all the necessary filters and spare parts required for the first two services, after the vehicle has been accepted.

OIJ BELLEVILLE BELLEVI